

SHARP

Be Original.

BP-30C25Z
BP-30C25ZT

Digital Full Colour Multifunctional System

Free to fit—Perfect for your business

High Productivity

- 100-sheet RSPF scans documents at 52 opm*¹ (one-sided)
- Multi bypass tray feeds paper up to 256 g/m² thick
- Print Release function enables printout from any compatible networked MFP*²
- Direct printing of Microsoft® Office (docx, xlsx, pptx) files*³ (option)
- OCR allows users to convert scanned documents into editable Office Open XML (docx, xlsx, pptx) files and searchable PDFs (option)
- Multicrop/Image Crop functions simultaneously scan multiple receipts/photos and save them as separate files
- Supports compact PDF (option)
- For large-volume scanned data, a URL can be generated and shared via e-mail
- Inbound routing lets you forward received faxes to a preset destination (option)

Exceptional Ease of Use

- Easy UI mode on 7.0-inch colour LCD touchscreen
- Dedicated user icons allow quick login to personalised operation screen
- Control panel tilts at various angles for easy access
- Red and green LED lamps light up to notify users of machine/job status
- Small footprint*⁴ (568 × 630 mm)
- Energy-saving functions include short warm-up time, power consumption of 0.5 W in fax/network standby, and more

Superb Image Quality

- Genuine Adobe® PostScript® 3™ (option)
- Sharp's proprietary Auto Colour Mode, further improved for enhanced scan performance
- Automatically makes scan settings according to document type—provides optimal scan results

Secure Information Sharing

- Secondary Ethernet port to support additional network*⁵
- Wireless connectivity enables easy access from mobile devices and flexible MFP placement (option)
- NFC*⁶ and QR Code® enable easy direct connection between MFP and mobile device
- Supports Sharpdesk Mobile print/scan application*⁷ and various mobile printing services (option)
- Application Portal offers apps for downloading and installing onto MFP
- Easy access to public cloud services such as OneDrive® for Business via single sign-on (option)
- Sends scanned data via Gmail™ or Microsoft Exchange/Online accounts
- Sharp OSA (Open Systems Architecture) allows integration with network and cloud-based applications (option)
- Advanced system/data protection and access control, including firmware self-recovery and whitelisting*⁸

*1: Originals per minute; when feeding A4 (8 1/2" x 11") sheets.

*2: Contact a Sharp customer representative for details on the recommended maximum number of connectable MFPs.

*3: This function is enabled via Qualcomm® DirectOffice™ technology.

*4: "Footprint" refers to the part directly adjacent to the floor or desk space. The numerical value is for the MFP's base unit only.

*5: Requires third-party Ethernet adaptor that supports two lines.

*6: The NFC interface is for Android™ devices running Android 9 or earlier. Requires third-party NFC card reader.

*7: Availability varies by country/region.

*8: Certain functions require optional equipment.



SPECIFICATIONS (tentative)

General	
Type	Desktop
Engine speed	A4 (8 1/2" x 11")*1: Max. 25 ppm A3 (11" x 17"): Max. 14 ppm
Control panel display	7.0-inch colour LCD touchscreen
Paper size	Max. A3W (12" x 18"), min. A6 (5 1/2" x 8 1/2")*2
Paper capacity (80 g/m²)	Standard: 350 sheets (250-sheet tray and 100-sheet multi bypass tray) Maximum: 1,850 sheets (350 sheets & optional 3 x 500-sheet tray)
Paper weight	Tray 1: 60 g/m² to 105 g/m² (16 lbs bond to 28 lbs bond) Trays 2-4 (BP-CS10/DE10): 60 g/m² to 220 g/m² (16 lbs bond to 80 lbs cover) Multi bypass tray: 55 g/m² to 256 g/m² (13 lbs bond to 140 lbs index)
Warm-up time*3	17 sec.*4
Memory	5 GB (copy/print shared) 128 GB SSD*5
Power requirements	Rated local AC voltage ±10%, 50/60 Hz
Power consumption	Max. 1.44 kW (110 V to 120 V), max. 1.84 kW (220 V to 240 V)
Dimensions (W x D x H)	568 x 630 x 653 mm (22 3/8" x 24 13/16" x 25 23/32")
Weight (approx.)	54 kg (119.1 lbs)

Copier	
Original paper size	Max. A3 (11" x 17")
First copy time*6	Colour: 11.0 sec. B/W: 8.0 sec.
Continuous copy	Max. 9,999 copies
Resolution	Scan (colour): 600 x 600 dpi Scan (B/W): 600 x 600 dpi, 600 x 400 dpi Print: 600 x 600 dpi, 9,600 (equivalent) x 600 dpi (depending on copy mode)
Gradation	Equivalent to 256 levels
Zoom range	25% to 400% (25% to 200% using RSPF) in 1% increments
Preset copy ratios	Metric: 10 ratios (5R/5E), inch: 8 ratios (4R/4E)

Colour Scanner	
Scan method	Push scan (via control panel) Pull scan (TWAIN-compliant application)
Scan speed*7	Colour & B/W: Max. 52 originals/min.
Resolution	Push scan: 100, 150, 200, 300, 400, 600 dpi Pull scan: 75, 100, 150, 200, 300, 400, 600 dpi 50 dpi to 9,600 dpi via user setting*8
File formats	TIFF, PDF, PDF/A-1a*9, PDF/A-1b, encrypted PDF, XPS, compact PDF*10*11, JPEG*11, searchable PDF*9, OOXML (pptx, xlsx, docx)*9, text (TXT [UTF-8])*9, rich text (RTF)*9
Scan destinations	Scan to e-mail/desktop*12/FTP server/network folder (SMB)/USB drive/local drive

• Design and specifications are subject to change without prior notice.
• Microsoft, OneDrive, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe in the US and/or other countries. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. Gmail and Android are trademarks of Google LLC. Mac is a trademark of Apple Inc., registered in the US and

Document Filing	
Document filing capacity*13	Main and custom folders: 5,000 pages or 500 files Quick file folder: 5,000 pages or 500 files
Stored jobs*14	Copy, print, scan, fax
Storage folders	Quick file folder, main folder, custom folder (max. 1,000 folders)
Printer	
Resolution	600 x 600 dpi, 9,600 (equivalent) x 600 dpi
Interface	USB 2.0 (host, high-speed), 10Base-T/100Base-TX/1000Base-T, wireless LAN (IEEE 802.11 b/g/n)*15
Supported OS*16	Windows Server® 2012, Windows Server® 2012 R2, Windows Server® 2016, Windows Server® 2019, Windows® 8.1, Windows® 10 Mac OS 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15 TCP/IP
Network protocols	LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP, SMB, WSD
Printing protocols	Standard: PCL 6 emulation Option: Adobe® PostScript® 3™
PDL	
Available fonts	80 fonts for PCL, 139 fonts for Adobe PostScript 3


Facsimile (requires optional MX-FX15)	
Compression method	MH/MR/MMR/JBIG
Communication protocol	Super G3/G3
Transmission time	Less than 3 seconds*17
Modem speed	33,600 bps to 2,400 bps with automatic fallback
Transmission resolution	From Standard (203.2 x 97.8 dpi) to Ultra Fine (406.4 x 391 dpi)
Recording size	A3 to A5 (11" x 17" to 5 1/2" x 8 1/2")
Memory	1 GB (built-in)
Greyscale levels	Equivalent to 256 levels

*1: Long-edge feeding. *2: Only short-edge feeding can be used with 5 1/2" x 8 1/2" paper. *3: In a standard measurement environment. May vary depending on operating conditions and environment.
*4: When starting the MFP via the power button. 28 seconds when starting via the main power switch.
*5: SSD capacity depends on procurement and sourcing status. *6: Long-edge feeding of A4 (8 1/2" x 11") sheets from 1st paper tray, using document glass, MFP in fully ready condition. May vary depending on operating conditions and environment. *7: Based on Sharp's A4 standard chart, using document feeder, long-edge feeding, one-sided scanning, and factory default settings. Scan speed will vary depending on the type of document and the scan settings. *8: Resolution will vary depending on the size of the scanned area. *9: Requires optional MX-EB20. *10: Requires optional MX-EB19. *11: Colour/greyscale only. *12: Requires Network Scanner Tool Lite. *13: Storage capacity will vary depending on the type of document and the scan settings. *14: Some features require optional equipment. *15: Requires optional MX-EB18. Availability of this option varies by country/region. *16: Mac OS requires optional MX-PK13. *17: Based on Sharp's standard chart with approx. 700 characters (A4 or 8 1/2" x 11" long-edge feeding) at standard resolution in Super G3 mode, 33,600 bps, JBIG compression.

other countries. PCL is a registered trademark of Hewlett-Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners.

Qualcomm® DirectOffice™

SYSTEM CONFIGURATION



Distributed by:

SHARP



GLOBAL SERVICES

The Wide Experience

©SHARP CORPORATION (DEC. 2020)

V.A.O. Complex, 198/103, Big Bazaar Street, Kumbakonam - 612001



0435 - 2422818, 2426818, 97151 51977



97151 51977



www.globalserviceskmu.com



info@globalserviceskmu.com