

## High-volume Document Performance You Can Trust

### High Productivity

- Flexible configuration with a wide selection of finishing options for saddle stitching, multi-folding, post-sheet insertion, and trimming
- Accommodates standard paper sizes up to SRA3/A3W (12" x 18"), custom sizes up to 320 x 470 mm (12 1/2" x 18 1/2"), and paper thicknesses up to 300 g/m<sup>2</sup>
- Empty toner cartridge can be replaced without interrupting a copy/print job
- 300-sheet DSPF scans documents at 240 opm<sup>\*1</sup> (two-sided)
- DSPF handles paper up to 220 g/m<sup>2</sup> thick
- Business card feeder on DSPF scans batches of up to 150 cards and lets you create business card databases via OCR
- Fiery<sup>®</sup> Server (option) for managing busy on-demand printing environments
- Print Release function enables printout from any compatible networked MFP<sup>\*2</sup>
- Direct printing of Microsoft<sup>®</sup> Office (docx, xlsx, pptx) files<sup>\*3</sup>

### Exceptional Ease of Use

- DSPF pauses operation when it detects skewed or multiple sheets being fed in
- DSPF signals that document is placed ready for scanning and reminds user to retrieve document after scanning
- Easy UI mode on 15.4-inch colour LCD touchscreen brings smooth and intuitive operation
- Control panel tilts from front to back and from side to side, and its supporting arm can be rotated freely from side to side
- Dedicated user icons allow quick login to personalised operation screen

### Superb Image Quality

- True 1,200 × 1,200 dpi printing
- Automatically makes scan settings according to document type—provides optimal scan results

### Secure Information Sharing

- Secondary Ethernet port to support additional network<sup>\*4</sup>
- Supports AirPrint printing service
- Application Portal<sup>\*5</sup> offers apps for downloading and installing onto MFP
- Easy access to public cloud services via single sign-on (option)
- Sends scanned data via Gmail<sup>™</sup> or Microsoft Exchange/Online<sup>\*6</sup> accounts
- Sharp OSA (Open Systems Architecture) allows integration with network and cloud-based applications (option)
- Advanced system/data protection and access control, including firmware self-recovery and whitelisting

<sup>\*1</sup>: Originals per minute; when feeding A4 (8 1/2" x 11") sheets. <sup>\*2</sup>: Contact a Sharp customer representative for details on the recommended maximum number of connectable MFPs.

<sup>\*3</sup>: This function is enabled via Qualcomm<sup>®</sup> DirectOffice<sup>™</sup> technology. <sup>\*4</sup>: Requires third-party Ethernet adaptor that supports two lines. <sup>\*5</sup>: Contact a Sharp customer representative for details. <sup>\*6</sup>: Exchange Server 2010/2013/2016, Exchange Online



## SPECIFICATIONS (tentative)

General	
Type	Console
Engine speed	A4 (8 1/2" x 11") <sup>*1</sup> : Max. 120/105 ppm A3 (11" x 17") <sup>*</sup> : Max. 54/52 ppm SRA3: Max. 52/49 ppm
Control panel display	15.4-inch colour LCD touchscreen
Paper size	Max. SRA3/A3W (12" x 18"), min. A5 (5 1/2" x 8 1/2") <sup>*2</sup>
Paper capacity (80 g/m <sup>2</sup> )	Standard: 3,100 sheets <sup>*3</sup> (1,200-sheet tray, 800-sheet tray, 500-sheet tray x 2, and optional 100-sheet multi bypass tray) Maximum: 13,500 sheets (3,000 sheets & optional 2 x 2,500-sheet tray x 2 and 500-sheet multi bypass tray)
Paper weight	Tray 1&2: 60 g/m <sup>2</sup> to 105 g/m <sup>2</sup> (16 lbs bond to 28 lbs bond) Tray 3&4: 60 g/m <sup>2</sup> to 220 g/m <sup>2</sup> (16 lbs bond to 80 lbs cover) Multi bypass tray: [MX-MFX1] 52 g/m <sup>2</sup> to 300 g/m <sup>2</sup> (13 lbs bond to 110 lbs cover) [MX-MF11] 52 g/m <sup>2</sup> to 220 g/m <sup>2</sup> (13 lbs bond to 80 lbs cover) Large capacity tray: [MX-LC12] 60 g/m <sup>2</sup> to 220 g/m <sup>2</sup> (16 lbs bond to 80 lbs cover) [MX-LC13 N] 52 g/m <sup>2</sup> to 300 g/m <sup>2</sup> (13 lbs bond to 110 lbs cover) 200 sec. <sup>*5</sup>
Warm-up time <sup>*4</sup>	
Memory	6 GB (copy/print shared) 1 TB HDD <sup>*6</sup>
Power requirements	AC 220 V to 240 V, 13 A, 50/60 Hz
Power consumption (max.)	Max. 2.99 kW (220 V to 240 V)
Dimensions (W x D x H) <sup>*7</sup>	1,099 x 775 x 1,529 mm (43 9/32" x 30 33/64" x 60 13/64")
Weight (approx.)	276 kg (608.5 lbs)

Copier	
Original paper size	Max. A3 (11" x 17")
First copy time <sup>*8</sup>	3.2 sec.
Continuous copy	Max. 9,999 copies
Resolution	Scan: 600 x 600 dpi, 600 x 400 dpi Print: 1,200 x 1,200 dpi, 600 x 600 dpi
Gradation	Equivalent to 256 levels
Zoom range	25% to 400% (25% to 200% using DSPF) in 1% increments
Preset copy ratios	Metric: 10 ratios (5R/5E), inch: 8 ratios (4R/4E)

Scanner	
Scan method	Push scan (via control panel) Pull scan (TWAIN-compliant application)
Scan speed <sup>*9</sup> (colour & B/W)	One-sided: Max. 120 originals/min. Two-sided: Max. 240 originals/min.
Resolution	Push scan: 100, 150, 200, 300, 400, 600 dpi Pull scan: 75, 100, 150, 200, 300, 400, 600 dpi 50 dpi to 9,600 dpi via user setting <sup>*10</sup>
File formats	TIFF, PDF, PDF/A-1a, PDF/A-1b, encrypted PDF, XPS, compact PDF <sup>*11</sup> , JPEG <sup>*11</sup> , searchable PDF, OOXML (pptx, xlsx, docx), text (TXT [UTF-8]), rich text (RTF)
Scan destinations	Scan to email/desktop <sup>*12</sup> /FTP server/network folder (SMB)/USB drive/local drive

Document Filing	
Document filing capacity <sup>*13</sup>	Main and custom folders: 35,000 pages or 5,000 files Quick file folder: 10,000 pages or 1,000 files
Stored jobs	Copy, print, scan
Storage folders	Quick file folder, main folder, custom folder (max. 1,000 folders)

Printer	
Resolution	1,200 x 1,200 dpi, 600 x 600 dpi
Interface	USB 2.0 (host, high-speed), 10Base-T/100Base-TX/1000Base-T
Supported OS	Windows Server® 2012, Windows Server® 2012 R2, Windows Server® 2016, Windows Server® 2019, Windows® 8.1, Windows® 10, Mac OS 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15, 11
Network protocols	TCP/IP
Printing protocols	LPR, Raw TCP (port 9100), POP3 (email printing), HTTP, FTP for downloading print files, IPP, SMB, WSD
PDL	PCL 6 emulation, Adobe® PostScript® 3™
Available fonts	80 fonts for PCL, 139 fonts for Adobe PostScript 3


Fiery® Server (requires optional MX-PE16, MX-PX16, and MX-KB18)	
Type	External server
System software	Fiery FS400 Pro
Operating system	Windows® 10
CPU	Intel® Pentium® G5400, 3.7 GHz
Memory	8 GB DDR SDRAM 500 GB HDD
Resolution	1,200 x 1,200 dpi, 600 x 600 dpi (PS, PCL)
Supported OS	Windows Server® 2016, Windows Server® 2019, Windows® 8.1 <sup>*14</sup> , Windows® 10, Mac OS 10.14, 10.15, 11
Network protocols	TCP/IP, LDAP, IPX iPrint
Interface	Gigabit Ethernet
Printing protocols	LPD, PAP, SMB, port 9100, IPP, FTP printing, email print, WSD
PDL	Adobe® PostScript® 3™
Available fonts	138 fonts for Adobe PostScript 3
Power requirements	AC 100 V to 240 V, 50/60 HZ
Power consumption	Max. 80 W
Dimensions (W x D x H)	248 x 204 x 384 mm (9 49/64" x 8 3/64" x 15 1/8")
Weight (approx.)	5.9 kg (13.0 lbs)

- \*1: Long-edge feeding.  
\*2: Only short-edge feeding can be used with A5 (5 1/2" x 8 1/2") paper.  
\*3: Paper capacity on minimum configuration.  
\*4: In a standard measurement environment. May vary depending on operating conditions and environment.  
\*5: When starting the MFP via the power button. 213 seconds when starting via the main power switch.  
\*6: HDD capacity depends on procurement and sourcing status.  
\*7: Including adjusters and protuberances.  
\*8: Long-edge feeding of A4 (8 1/2" x 11") sheets from 2nd paper tray, using document glass, MFP in fully ready condition. May vary depending on operating conditions and environment.  
\*9: Based on Sharp's A4 standard chart, using document feeder, long-edge feeding, and factory default settings. Scan speed will vary depending on the type of document and the scan settings.  
\*10: Resolution will vary depending on the size of the scanned area.  
\*11: Colour/greyscale only.  
\*12: Requires Network Scanner Tool Lite.  
\*13: Storage capacity will vary depending on the type of document and the scan settings.  
\*14: For printer driver only.

- Design and specifications are subject to change without prior notice.  
• Fiery is a registered trademark of Electronics for Imaging, Inc. in the US and/or certain other countries. Microsoft, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Gmail is a trademark of Google LLC. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett-Packard Company. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe in the US and/or other countries. Intel and Pentium are trademarks of Intel Corporation or its subsidiaries in the US and/or other countries. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners.

Qualcomm® DirectOffice™

## SYSTEM CONFIGURATION



Certain optional equipment may not be available in some areas.

SHARP

Distributed by:  
**GLOBAL SERVICES**  
The Wide Experience

V.A.O. Complex, 198/103, Big Bazaar Street, Kumbakonam - 612001

0435 - 2422818, 2426818, 97151 51977 97151 51977 www.globalserviceskmu.com info@globalserviceskmu.com

©SHARP CORPORATION (MAY 2021)